Certificate

Linear Gap Seals Scheme

Certificate Number: IFCC 2051

Initial Certification:	22 September 2025	**Revised:**	17 February 2026
Valid to:	24 April 2030	**Issue No:**	2

Issued by **IFC Certification Ltd** part of the Kiwa UK Group

This is to certify that

Siderise Insulation Ltd

Forge Industrial Estate
Maesteg
Bridgend CF34 OAH
Telephone: 01656 730833

Who fabricate the following systems:

Siderise IC-CB / IC-FS Cavity Barriers and Perimeter Firestops

has satisfied the requirements of the SDP 14 Linear Gap Seals scheme v1.5. This includes the testing of products to **BS EN 1366-4:2006+A1:2010**, the inspection of their Factory Production Control continuing surveillance audits and testing of samples of products taken from production. The product specification and reports are detailed below and in the tables on pages 2 and 3 of this certificate.

Report numbers in italics refer to tests where products have been tested generally in accordance with the standard; in which case the test result is only valid to the specimen as tested.

Test reports: 431532, *551364*, *398827/R*, *408622*, *424137A*, *424701*

David Mowatt
Head of IFC Certification /
Kiwa UK

kiwa CERTIFIED Product Scheme IFC Certification

UKAS PRODUCT CERTIFICATION 0175

Certificate is only valid if verified on the website.
Check the validity of this certificate by scanning this QR Code or visiting www.ifccertification.com/search/

KIWA
IFC Certification Ltd
Ground Floor, Suite A
Building 2,
Bear Brook Office Park
Walton Street, Aylesbury,
Bucks, HP21 7GQ

Certificate

Certificate Number: IFCC 2051 issue 2

The production of fire-resistant products are manufactured in accordance with the assessment / test reports referenced within the following tables:

Horizontal

Product / Test Reports	Seal thickness (mm)	Cover length (mm)	Compression minimum	Integrity (mins)	Insulation (mins)	Gap width (mm)	Fixing Type	Qty brackets	Fixing centres (mm)
IC-CB30 431532 (H) *424137A (A)*	75	1200	+ 10%	90	30	20-50	No bracket	0	N/A
			+ 10mm			51-150	B65/110	2	600
						151-250	B195		
IC-CB30X *551364 (B)*	90					251-400	B355		

Product / Test Reports	Seal thickness (mm)	Cover length (mm)	Compression minimum	Integrity (mins)	Insulation (mins)	Gap width (mm)	Fixing Type	Qty brackets	Fixing centres (mm)
IC-FS60 431532 (G) *408622 (A)*	100	1200	+ 10%	90	60	20-50	No bracket	0	N/A
			+ 10mm			51-150	B65/110	2	600
						151-250	B195		
IC-FS60X *551364 (B)*	120					251-400	B355		

Product / Test Reports	Seal thickness (mm)	Cover length (mm)	Compression minimum	Integrity (mins)	Insulation (mins)	Gap width (mm)	Fixing Type	Qty brackets	Fixing centres (mm)
IC-FS120 431532 (F) *424137A (B)*	120	1200	+ 10%	120	120	20-50	No bracket	0	N/A
			+ 10mm			51-150	B65/110	2	600
						151-250	B195		
IC-FS120X *551364 (A)*	150					251-400	B355		

Signed on behalf of Kiwa UK



David Mowatt
Head of IFC Certification /
Kiwa UK

Certificate

Vertical

Product / Test Reports	Seal thickness (mm)	Cover length (mm)	Compression minimum	Integrity (mins)	Insulation (mins)	Gap width (mm)	Fixing Type	Qty brackets	Fixing centres (mm)
IC-CB30 431532 (D)	75	1200	+ 10%	90	30	20-50	No bracket	0	N/A
398827/R (B)			+ 10mm			51-150	B65/110	2	600
						151-250	B195		
IC-CB30X *424701 (B)*	90					251-400	B355		

Product / Test Reports	Seal thickness (mm)	Cover length (mm)	Compression minimum	Integrity (mins)	Insulation (mins)	Gap width (mm)	Fixing Type	Qty brackets	Fixing centres (mm)
IC-FS60 431532 (C)	100	1200	+ 10%	90	60	20-50	No bracket	0	N/A
424701 (B)			+ 10mm			51-150	B65/110	2	600
						151-250	B195		
IC-FS60X *398827/R (A)*	120					251-400	B355		

Product / Test Reports	Seal thickness (mm)	Cover length (mm)	Compression minimum	Integrity (mins)	Insulation (mins)	Gap width (mm)	Fixing Type	Qty brackets	Fixing centres (mm)
IC-FS120 431532 (B)	120	1200	+ 10%	120	120	20-50	No bracket	0	N/A
398827/R (A)			+ 10mm			51-150	B65/110	2	600
						151-250	B195		
IC-FS120X *398827/R (A)*	150					251-400	B355		

i. All cavity barriers tested to EN1366-4
ii. All brackets to be suitably fixed to substrate with non-combustible fixings
iii. All brackets to penetrate product at mid-thickness
iv. All brackets to penetrate to a depth of 75% of the gap width
v. Galvanised steel brackets or stainless-steel brackets

Signed on behalf of Kiwa UK

David Mowatt
Head of IFC Certification /
Kiwa UK